

You can view this page in:

- EN
- DE
- SV
- FI
- C6
- DA
- EL
- ES
- FR
- HU
- IT
- JA
- KO
- NL
- NO
- PL
- PT
- RU
- SK
- TR
- ZH

Detailed information for: AF38Z-22-00-22

This page contains technical data sheet, documents library and links to offering related to this product. If you require any other information, please contact us using form located at the bottom of the page.

 [Print...](#)

 [Print to Pdf...](#)

[Data Sheet](#)

[Downloads](#)

AF38Z-22-00-22

General Information

Extended Product Type: AF38Z-22-00-22

Product ID: 1SBL296501R2200

EAN: 3471523116924

Catalog Description: AF38Z-22-00-22 48-130V50/60HZ-DC Contactor

Long Description: The AF38Z-22-00-22 is a 4 pole - 690 V IEC or 600 UL contactor with screw terminals, controlling motors up to 11 kW / 400 V AC (AC-3) and switching power circuits up to 55 A (AC-1) or 55 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (48-130 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.

Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Across the Line Contactors



Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900
Popular Downloads	
Instructions and Manuals:	1SBC101027M6801
Dimensions	
Product Net Width:	45 mm
Product Net Depth / Length:	101 mm
Product Net Height:	86 mm
Product Net Weight:	0.4 kg
Technical	
Number of Main Contacts NO:	2
Number of Main Contacts NC:	2
Number of Auxiliary Contacts NO:	0
Number of Auxiliary Contacts NC:	0
Standards:	IEC 60947-1 / 60947-4-1 and EN 60947-1 / 60947-4-1, UL 508, CSA C22.2 N°14
Rated Operational Voltage:	Main Circuit 690 V
Rated Frequency (f):	Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-4-1, Open Contactors q = 40 °C 55 A
Rated Operational Current AC-1 (I_e):	(690 V) 40 °C 55 (690 V) 60 °C 45 A (690 V) 70 °C 37
Rated Operational Current AC-3 (I_e):	(415 V) 60 °C 21.2 A (440 V) 60 °C 20 A (500 V) 60 °C 17.6 A (690 V) 60 °C 10.5 A (380 / 400 V) 60 °C 22 A (220 / 230 / 240 V) 60 °C 23.2 A
Rated Operational Power AC-3 (P_e):	(400 V) 11 kW (415 V) 11 kW (440 V) 11 kW (500 V) 11 kW (690 V) 9 kW (220 / 230 / 240 V) 5.5 kW
Rated Short-time Withstand Current (I_{cw}):	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 55 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 150 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 450 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 225 A for 1 s -empty- A
Maximum Electrical Switching Frequency:	(AC-1) 600 cycles per hour
Rated Insulation Voltage (U_i):	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Rated Control Circuit Voltage (U_{50 Hz}):	48 ... 130 V

c): 50 Hz / 60 Hz 48 ... 130 V
60 Hz 48 ... 130 V
DC Operation 48 ... 130 V

Operate Time:	Between Coil De-energization and NC Contact Closing 13 ... 98 ms Between Coil De-energization and NO Contact Opening 11 ... 95 ms Between Coil Energization and NC Contact Opening 38 ... 90 ms Between Coil Energization and NO Contact Closing 40 ... 95 ms
----------------------	--

Connecting Capacity Main Circuit:	Flexible with Ferrule 1/2x 1.5 ... 16 mm ² Flexible with Insulated Ferrule 1x 1.5 ... 16 mm ² Flexible with Insulated Ferrule 2x 1.5 ... 16 mm ² Rigid 1/2x 1.5 ... 16 mm ²
--	--

Connecting Capacity Control Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 1 ... 2.5 mm ²
---	---

Wire Stripping Length:	Control Circuit 10 mm Main Circuit 12 mm
-------------------------------	---

Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
------------------------------	--

Terminal Type:	Screw Terminals
-----------------------	-----------------

Technical UL/CSA

General Use Rating UL/CSA:	(600 V AC) 55 A
-----------------------------------	-----------------

Tightening Torque UL/CSA:	Control Circuit 11 IA Main Circuit 22 IA
----------------------------------	---

Environmental

Ambient Air Temperature:	Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air -40 ... +70 °C
---------------------------------	--

Climatic Withstand:	Category B according to IEC 60947-1 Annex Q
----------------------------	---

Maximum Operating Altitude Permissible:	3000 m
--	--------

Resistance to Vibrations acc. to IEC 60068-2-6:	5 ... 300 Hz 4 g closed position / 2 g open position
--	--

Resistance to Shock acc. to IEC 60068-2-27:	Closed, Shock Direction: A 30 K40 Closed, Shock Direction: B1 25 K40 Closed, Shock Direction: B2 15 K40 Closed, Shock Direction: C1 25 K40 Closed, Shock Direction: C2 25 K40 Open, Shock Direction: A 25 K40 Open, Shock Direction: B1 5 K40 Open, Shock Direction: B2 10 K40 Open, Shock Direction: C1 20 K40 Open, Shock Direction: C2 20 K40
--	---

RoHS Status:	Following EU Directive 2011/65/EU
---------------------	-----------------------------------

Certificates and Declarations (Document Number)

ABS Certificate:	ABS_15-GE1349500-PDA_90682247
-------------------------	---

CB Certificate:	CB_SE-96553
------------------------	-----------------------------

CCC Certificate:	CCC_2010010304445623
-------------------------	--------------------------------------

CQC Certificate:	CQC2010010304445623 CQC2020010304294316
-------------------------	--

Declaration of Conformity - CCC:	2020980304001254 2020980304001052
---	--

Declaration of Conformity - CE:	1SBD250001U1000
--	---------------------------------

DNV Certificate:	DNV-GL_TAE00001AF-3
-------------------------	-------------------------------------

DNV GL Certificate:	DNV-GL_TAE00001AF-3
EAC Certificate:	EAC_RU_FRME77B03447
Environmental Information:	1SBD250153E1000
GL Certificate:	DNV-GL_TAE00001AF-3
GOST Certificate:	GOST_POCCFR.ME77.B07175.pdf
Instructions and Manuals:	1SBC101027M6801
KC Certificate:	KC_HW02016-15002C
LR Certificate:	LRS_1300087E1
RINA Certificate:	RINA_ELE084013XG
RMRS Certificate:	RMRS_1802705280
RoHS Information:	1SBD250001U1000
UL Certificate:	UL_20171228-E319322_3_1
UL Listing Card:	UL_E319322

Container Information

Package Level 1 Units:	box 1 piece
Package Level 1 Width:	87 mm
Package Level 1 Depth / Length:	103 mm
Package Level 1 Height:	47 mm
Package Level 1 Gross Weight:	0.4 kg
Package Level 1 EAN:	3471523116924
Package Level 2 Units:	box 18 piece
Package Level 2 Width:	250 mm
Package Level 2 Depth / Length:	300 mm
Package Level 2 Height:	315 mm
Package Level 2 Gross Weight:	14.4 kg
Package Level 3 Units:	864 piece

Classifications

Object Classification Code:	Q
ETIM 4:	EC000066 - Magnet contactor, AC-switching
ETIM 5:	EC000066 - Magnet contactor, AC-switching
ETIM 6:	EC000066 - Power contactor, AC switching
ETIM 7:	EC000066 - Power contactor, AC switching
eClass:	V11.0 : 27371003
UNSPSC:	39121529
E-Number (Finland):	3705858

Contact us

Submit your inquiry and we will
contact you

[CONTACT US](#)

Or contact your [ABB Contact Center](#)