

# 44 Series

## Electromechanical Totalizer



A 6 figure, non-reset counter. Metal/plastic frame assembly assures ruggedness while one piece cover discourages tampering. Precision molded internal gearing requires no lubrication for long, accurate count life. Applications include warranty verification, electronic game counting, coin box tallies, or wherever small size, highly visible numerals, and solid construction are critical.

### Key Features

- Small size
- Highly visible numerals
- Solid construction
- Options include:
  - Voltages
  - 7 figure
  - Lead length
  - Special connectors
  - Extended temperature range
  - Count x 2

### Applications


- Vending / gaming machines
- Warranty verification
- Coin box tallies

### Specifications

<b>Figures</b>	6 figures, white on black, 0.18" [4.6mm] high
<b>Reset</b>	Non-reset
<b>Speed</b>	600 counts/minute (min.50ms–on,50ms–off)
<b>Voltage</b>	115VAC, 24VDC (+/- 10%, but not to exceed 10 volts)
<b>Power</b>	1.5 watts (nominal)
<b>Mount</b>	Rear, behind the panel, base, or combination
<b>Terminations</b>	(2) #22 AWG 221°F [105°C] wire leads, 10" [254mm] long
<b>Operating Life</b>	Beyond 3 million counts
<b>Temp. Range</b>	+23°F to +104°F [-5°C to + 40°C]
<b>Approvals</b>	UL Recognized, CE Compliant
<b>Weight</b>	2.5 oz. [71g]


## Dimensions

### Rear Mount




Mounting hole: For M3 screw

### Behind the Panel Mount




Mounting holes: For M3 self tapping screw

### Snap-In Panel Mount



### Base Mount



Mounting holes: 0.14" [3.6mm] Dia.

## Part Numbers

<b>2-4416</b>	115VAC, 6 figure, rear mount
<b>8-4416</b>	24VDC, 6 figure, rear mount
<b>R2-4416</b>	115VAC, 6 figure, behind the panel mount
<b>R8-4416</b>	24VDC, 6 figure, behind the panel mount
<b>V2-4416</b>	115VAC, 6 figure, base mount
<b>V8-4416</b>	24VDC, 6 figure, base mount
<b>RV2-4416</b>	115VAC, 6 figure, combination mount
<b>RV8-4416</b>	24VDC, 6 figure, combination mount

