

REDINGTON COUNTERS, INC.  
P.O. Box 608, 130 Addison Road, Windsor, CT 06095  
Toll Free: (860) 688-6205 • Fax: 860/688-1591  
E-Mail: Info@RedingtonCounters.com • Website: www.RedingtonCounters.com

**Item # SR8-4817, Model 48 Electromechanical Totalizer**



**Model 48 Electromechanical Totalizer**

A compact, economical, 6 or 7 figure, non-reset, electromechanical counter designed for general purpose industrial and commercial counting applications. It is designed for a variety of mounting methods as required by the application. Commonly used for coin-operating equipment, photocopiers and vending machines.

**SPECIFICATIONS**

Model No.	48
Mounting	SR Panel Mount
Display	7 Figures, white on black, 0.17 inch (4.3mm) high
Display Height	0.17 Inch
Display Height	4.3 mm
No. of Digits	7
Voltage	24 VDC
Power	2 watts
Reset Type	none
Speed	1000 counts/minute AC, (min. 30ms - on, 30ms - off); 1200 counts/minute DC, (min. 25ms - on, 25ms - off)
Operating Temperature	-15 to +140 &#176F
Operating Temperature	-26 to +60 &#176C
Approvals	UL Recognized, CSA Certified, CE Compliant
Termination	(2) No. 22 AWG 105&#176C wire leads, 12 inch (305mm) long.
Panel Cutout	1.67 x 1.29 Inch
Panel Cutout	42.4 x 32.8 mm
Weight	3.5 oz
Weight	99 gm
Operating Life	Beyond 10 million counts

Stock Availability	No
Maximum Panel Thickness	0.04 to 0.08 (Recommended) Inch
Maximum Panel Thickness	1.0 to 2.0 (Recommended) mm