



- [Circuit Board Indicators](#)
- [Panel Mount Indicators](#)
- [Solid State Lighting](#)
- [Traffic Signals](#)
- [Vehicle Lighting](#)
- [Rail](#)
- [Obstruction Lighting](#)
- [Hazardous Area Lighting](#)
- [Heliport Lighting](#)

Circuit Board Indicators - Through Hole Indicators	
P/N# 5219340F	3 mm Lens Single Color
Description	Discrete LED Lamp
Package Options	100 pieces per bag
Product Type	Through Hole Indicators
Sub Product Type	Discrete LED
Configuration	3 mm Lens
Lamp Type	Single Color
Lens Color	Diffused
Viewing Angle	60 degrees
Test Current (mA)	10mA

Absolute Maximum Ratings (Ta = 25 °)	
Forward Current Continuous	30 mA
Forward Current Pulse	90 mA
Derating	from 25Å° @ 1.8mW/Å°C
Reverse Voltage	5 V
Solder Temp	260Å° for 5 sec
Operating Temp	-55~+100° C
Storage Temp	-55~+100° C
Peak Wave Length	635

Distributor Stock Check

Check stock with our distributors now.

5219340F

[check stock](#)

how to purchase


- [sales contacts](#)
- [stock check](#)

search

[Product Line Search](#)

Please select a Product Line to search.

[find](#)



Operating Characteristics

LED Position	
Color	Red
Lamp Type	Single Color
LED Type	GaAsP/GaP
Intensity Min (mcd)	8.6
Intensity Typ (mcd)	11.0
Intensity Max (mcd)	
Fwd Voltage Min	1.5
Fwd Voltage Typ	2.2
Fwd Voltage Max	3.0
Dom Wavelength Min (nm)	
Dom Wavelength Typ (nm)	
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	135
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

Part # / Text Search

Part No.:

Text Search:

[search](#)

quick links

- [Dialight Corporate Video](#)
- [Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. **View PDF File**](#)
- [Application Notes](#)
- [FAQs](#)
- [Dialight Ltd \(UK\)](#)
- [Dialight Garufo](#)
- [Dialight BLP](#)
- [LumiDrives](#)