


HEAT SHRINK TUBING



✓ Active

TE CONNECTIVITY
ZH2-5.0-0-SP-SM

Raychem | ZH2

ZH2-5.0-0-SP-SM
 TE Internal Number: A44820-000
 Alias ID: 8-1202020-2

Always EU RoHS/ELV Compliant

Wall Type **Single**

Resistant To **Abrasion**

Product Source **US**

Packaging Method **Spool**

Shrink Ratio **2:1**

Catalog Pages/Data Sheets

[ZH2 Pages From 9-1773447-9](#)

PDF
English

Product Specifications

Product Specification

[ZEROHAL ZH2 And ZH4 Tubing Polyolefin, Flexible, Heat-Shrinkable, Flame Retardant](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features	Wall Type	Single
Body Features	Shrink Ratio	2:1
	Color	Black
	Material	ZEROHAL Polyolefin
	Fluid Type	Water
Dimensions	Recovered Wall Thickness (Nominal)	.56 mm [.022 in]
	Recovered Inside Diameter (Max)	2.5 mm [.098 in]
	Expanded Inside Diameter (Min)	5.3 mm [.209 in]
Usage Conditions	Resistant To	Abrasion
	Operating Temperature Range (°C)	EE 105

Operating Temperature Range (°C) **-55 - 105**

Flammability **Flame-Retardant**

Fluid Resistance **Moisture/Spray Protection**

Shrink Temperature (Min) (°C) **70**

Packaging Features

Packaging Method

Spool

Other

Product Source

US

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)