



DIP SOCKETS ICA SERIES

Mates with:
AP, APS, APO,
APA, APE

ICA	ROW SPACING & NO. OF CONTACTS	STYLE OPTION	PLATING OPTION	OPTION (Leave Blank for Standard Version)
-----	-------------------------------	--------------	----------------	-------------------------------------------

Specify from chart below

- Side & end stackable
- Great for auto insertion
- Open body design

Style	Row Space	No. of Contacts
-308	.300 (7,62)	08
-314	.300 (7,62)	14
-316	.300 (7,62)	16
-318	.300 (7,62)	18
-320	.300 (7,62)	20
-322*	.300 (7,62)	22
-324	.300 (7,62)	24
-328	.300 (7,62)	28
-422	.400 (10,16)	22
-624	.600 (15,24)	24
-628	.600 (15,24)	28
-632	.600 (15,24)	32
-640	.600 (15,24)	40
-648	.600 (15,24)	48

*-322 has no cross bar on one end.

GG
= 30μ" (0,76μm)
Gold contact,
10μ" (0,25μm)
Gold Shell

GT
= 30μ" (0,76μm)
Gold contact,
Tin Shell

TT
= Tin contact
and shell
(-S, -ZS, -W,
-ZW only)

ST
= 10μ" (0,25μm)
Gold contact,
Tin shell (Styles -S
& -ZS only)

-2
= .360 (9,14)
Tail
Wire-Wrap Option
Requires Style
-W or -ZW
Specify desired
suffix for shorter
Wire-Wrap tail.

-3
= .260 (6,60)
Tail
-L
= Locking
Socket
Requires Style
-S or -ZS
Requires GT
Plating Option

ALSO AVAILABLE
RoHS compliant options.
Call Samtec.
DIP Adaptors.
Request ICA Fact Sheet.

SPECIFICATIONS
For complete specifications see www.samtec.com?ICA

Note: Some sizes, styles and options are non-standard, non-returnable.

Insulator Material: Black Glass Filled Polyester except -328 is LCP
Contact: BeCu
Shell: Brass except style K Phosphor Bronze
Plating: Au or Sn over 50μ" Ni
Flammability Rating: UL 94V-O
Insulation Resistance: 5000 MΩ min
Temperature Range: -55°C to +105°C with Tin -55°C to +125°C with Gold.
Withstanding Voltage: 1000 VRMS
Current Rating: 1A
Contact Resistance: 10mΩ max
Lead Size Range: .015" (0,38mm) to .022" (0,56mm) DIA and most IC leads
Insertion Force: (Single contact only) Standard = 9 oz avg, 16 oz max; Low Insertion Force = 2.5 oz avg, 5.5 oz max
Withdrawal Force: (Single contact only) Standard = 2.5 oz avg, 1.5 oz min; Low Insertion Force = 2.0 oz avg, 0.35 oz min
Lead-Free Solderable: Wave only
RoHS Compliant: No

-S, -ZS, -ZA, -J, or -K
= Printed Circuit
-ZS & -ZA = Low Insertion Force

LEAD STYLE	X DIA	Y TAIL	Z
-S or -ZS	(0,51) .020	(3,18) .125	(7,62) .300
-ZA	(0,51) .020	(4,57) .180	(8,89) .350
-J	(0,64) .025	(10,41) .410	(15,24) .600
-K	(0,89) .035	(12,95) .510	(17,86) .703

Insertion Depth = .095" (2,41) to .145" (3,68):
Style S Component Part No. = SC-1P1
Style ZS Component Part No. = EZ-1P1
Style ZA Component Part No. = EZ-6P1
Option L Component Part No. = SC-1L1 or EZ-1L1
Insertion Depth = .095" (2,41) to .138" (3,51)
Style J Component Part No. = SC-1P3
Insertion Depth = .125" (3,18) to .157" (3,99)
Style K Component Part No. = SC-2P1

Locking lead available with -S and -ZS. See OPTION.

-L Option

-W, -ZW
= Wire-Wrap
ZW = Low Insertion Force

Shorter wire-wrap tail lengths available. See OPTION.

Insertion Depth = .125" (3,18) to .157" (3,99)
Style W Component Part No. = SC-1W1(1)
Style ZW Component Part No. = SC-1W1(2)
Style ZW-2 Component Part No. = SC-1W1(3)
Style ZW-3 Component Part No. = EZ-1W1(3)

-ZE or -ZH
= Elevated
Low Insertion Force

LEAD STYLE	X DIA	W TAIL	Y	Z
-ZE	(0,51) .020	(4,32) .170	(8,86) .349	(13,77) .542
-ZH	(0,46) .018	(3,81) .150	(12,95) .510	(17,86) .703

Insertion Depth = .125" (3,18) to .170" (4,32)
Style ZE Component Part No. = EZ-2P3
Insertion Depth = .125" (3,18) to .145" (3,68)
Style ZH Component Part No. = EZ-2P2

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM