



Fork terminals with nylon insulation sleeves, recommended for temperatures up to 105°C. Inner bronze insulation grip sleeve lengthens flex radius of conductor and eliminates conductor creep. Nylon jacket is color-coded.

Stock thickness same as ring terminal of same size.

Nylon Insulated Fork—Insulation Grip



Cat. No.	Bulk Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Wt./lbs. Bolt Hole	Per 1000	Dimensions			
							A	B	C	M
RA18-6F	RA1103	100/1M	22-16	.136	#6	3	.83	.25	.25	.71
RA18-8F	RA1123	100/1M	22-16	.136	#8	3	.86	.31	.25	.71
RA18-10F	RA1153	100/1M	22-16	.136	#10	3	.86	.31	.25	.71
RA18-14F	RA1163	100/1M	22-16	.136	1/4"	4	.95	.44	.31	.70
RB14-6F	RB1113	100/1M	18-14	.162	#6	3 1/2	.87	.31	.25	.71
RB14-8F	RB1123	100/1M	18-14	.162	#8	3 1/2	.87	.31	.25	.71
RB14-10F	RB1153	100/1M	18-14	.162	#10	4	.87	.38	.25	.71
RB14-14F	RB1163	100/1M	18-14	.162	1/4"	4	.95	.44	.28	.74
—	RB1103	1000	18-14	.162	#6	6	.74	.28	.16	.60
—	RB1124	1000	18-14	.190	#8	6	.95	.31	.25	.79
—	RB1154	1000	18-14	.190	#10	6	.95	.31	.25	.79
RC10-6F	RC1113	50/500	12-10	.210	#6	6	.97	.31	.27	.81
RC10-8F	RC1123	50/500	12-10	.210	#8	6	1.00	.37	.27	.81
RC10-10F	RC1153	50/500	12-10	.210	#10	6	1.00	.37	.27	.81
RC10-14F	RC1163	50/500	12-10	.210	1/4"	6	1.12	.50	.27	.86
—	RC1124	1000	12-10	.250	#8	6	1.10	.37	.27	.91
—	RC1154	1000	12-10	.250	#10	6	1.10	.37	.27	.91

U.L. Listed E-9809

Installing tools: WT145C, WT2000, WT112M, ERG-2001, ERG-2003, WT145A, WT1455, WT2130A (RC)

Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (12050 tool and application dies). See page C61.

Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

For Mil Specs listing, please refer to page C73.