

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Product image





To feed through power, signal, and data is the classical requirement in electrical engineering and panel building. The insulating material, the connection system and the design of the terminal blocks are the differentiating features. A feed-through terminal block is suitable for joining and/or connecting one or more conductors. They could have one or more connection levels that are on the same potential or insulated against one another.

General ordering data

Version	SAK Series, Feed-through terminal, Rated cross- section: 35 mm ² , Screw connection
Order No.	0339860000
Туре	SAK 35/EN
GTIN (EAN)	4008190076573
Qty.	20 pc(s).
Delivery status	This article will no longer be available in the future.
Available until	2022-03-30
Alternative product	1020500000

Creation date March 12, 2024 4:08:45 PM CET

Catalogue status 09.03.2024 / We reserve the right to make technical changes.

Technical data

SAK 35/EN



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

Dimensions and weights			
Dauth	60 F	Dauth (inches)	
Depth	63.5 mm	Depth (inches)	2.5 inch
Height	58 mm	Height (inches)	2.283 inch
Width	18 mm	Width (inches)	0.709 inch
Net weight	53 g		
Temperatures			
			F 1 1 1
Storage temperature		Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex-
	-25 °C55 °C		Certificate of Conformity
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	100 °C
Material data			
Material	PA 66	Colour	beige / yellow
UL 94 flammability rating	V-2		
Rating data IECEx/ATEX			
Operating temperature range range see EC Design Test Certificate / IEC Ex- Certificate of Conformity		Marking EN 60079-7	Ex eb II C Gb
Ex 2014/34/EU label	II 2 G D		
System specifications			
Version	Screw connection,	End cover plate required	
Version	for screwable cross- connection, One end	End cover plate required	
	without connector		Yes
Number of potentials	1	Number of levels	1
Number of clamping points per level	2	Number of potentials per tier	1
Levels cross-connected internally	No	PE connection	No
Rail	TS 35, TS 32	N-function	No
PE function	No	PEN function	No
Additional technical data			
Explosion-tested version	No	Number of similar terminals	1
Type of mounting	Snap-on		I
	Shap-on		
CSA rating data			
Certificate No. (CSA)	154685-1501714	Current size C (CSA)	120 A
Voltage size C (CSA)	600 V	Wire cross section max. (CSA) 2 AWG	
Wire cross section min. (CSA)	12 AWG	, , , , , , , , , , , , , , , , ,	
· · ·			

Technical data



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

Blade size	6.5 x 1.2 mm	Clamping range, max.	50 mm²
Clamping range, min.	2.5 mm ²	Clamping screw	M 6
Connection cross-section, stranded,		Connection cross-section, stranded, mir	۱.
max.	max. 50 mm ²		4 mm ²
Connection direction	on side	Gauge to IEC 60947-1	B8
Number of connections	2	Stripping length	18 mm
Tightening torque, max.	5 Nm	Tightening torque, min.	4 Nm
Twin wire-end ferrules, max.	16 mm ²	Twin wire-end ferrules, min.	1.5 mm²
Type of connection		Wire connection cross section AWG,	
	Screw connection	max.	AWG 2
Wire connection cross section AWG, min.	AWG 12	Wire connection cross section, finely stranded, max.	35 mm²
Wire connection cross section, finely stranded, min.	2.5 mm ²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	35 mm²
Wire connection cross-section, finely	2.5 11111	Wire connection cross-section, finely	55 1111
stranded with wire-end ferrules DIN		stranded with wire-end ferrules DIN	
46228/1, min.	2.5 mm ²	46228/4, max.	35 mm²
Wire connection cross-section, finely		Wire connection cross-section, solid	
stranded with wire-end ferrules DIN 46228/4, min.	2.5 mm ²	core, max.	16 mm ²
Wire connection cross-section, solid core, min. 2.5 mm ²			
General			
Rail	TS 35, TS 32	Standards	IEC 60947-7-1
ire connection cross section AWG.		Wire connection cross section AWG,	
max.	AWG 2	min.	AWG 12
Rating data			
Rated cross-section	35 mm ²	Rated voltage	800 V
Rated DC voltage	800 V	Rated current	125 A
Current at maximum wires	150 A	Standards	IEC 60947-7-1
Volume resistance according to IEC		Rated impulse withstand voltage	
60947-7-x	0.26 mΩ		8 kV
Power loss in accordance with IEC 60947-7-x	4 W	Pollution severity	3
UL rating data			
0 (C + N (UD)	500000		
Certificate No. (UR)	E60693	Conductor size Factory wiring max. (UR	,
Conductor size Factory wiring min. (UR)		Conductor size Field wiring max. (UR)	2 AWG
Conductor size Field wiring min. (UR)	12 AWG	Current size C (UR)	115 A
Voltage size C (UR)	600 V		
Classifications			
ETIM 6.0	EC000897	ETIM 7.0	EC000897
ETIM 8.0	EC000897 EC000897	ETIM 9.0	EC000897 EC000897
ETIM 8.0 ECLASS 9.0			
	27-14-11-20	ECLASS 9.1	27-14-11-20
	07 14 11 00		07 1 / 4 4 0 0
ECLASS 10.0 ECLASS 12.0	27-14-11-20 27-14-11-20	ECLASS 11.0 ECLASS 13.0	27-14-11-20 27-25-01-01

Technical data



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

Approvals	
Approvals	
ROHS	Conform
UL File Number Search	UL Website
Certificate No. (UR)	E60693
Downloads	
Approval/Certificate/Document of Conformity	INMETRO certificate Declaration of Conformity UKCA declaration of conformity
Engineering Data	<u>CAD data – 10556_SAK_35-EN_DXF.dxf</u> <u>CAD data – STEP</u>
User Documentation	StorageConditionsTerminalBlocks
Catalogues	Catalogues in PDF-format



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

End plates are fitted to the open side of the last modular terminal before the end bracket. The use of an end plate ensures the function of the modular terminal and the

specified rated voltage. It guarantees protection against contact with live parts and makes the final terminal

Accessories

SAK-Series

SAK Series

General ordering data

Туре	AP SAK35/TW SAK16 BL	Version
Order No.	<u>0303680000</u>	SAK Series, End plate, 1.5 mm, blue
GTIN (EAN)	4008190025199	
Qty.	10 pc(s).	
Туре	AP SAK35/TW SAK16	Version
Type Order No.	AP SAK35/TW SAK16 0303660000	Version SAK Series, End plate, 1.5 mm, beige

finger-proof.

SAK-Series



Warning covers with a flash symbol provide more safety for man and machine. They are used where external voltage must be indicated within the application.

	<u>v</u>	
Туре	AD 4 SAK35	Version
Order No.	<u>0178700000</u>	SAK Series, cover plate, yellow, 71.6 mm
GTIN (EAN)	4008190056414	
Qty.	50 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Marker holder



The marker holder offer the possibility of additional mounting of standard markers with a pitch of 5 or 5.1 mm. The angled holders can be optionally snaped together and could be mounted in all standard marking channels of the Klippon[®] Connect modular terminal blocks. Fitting marker types could be found under the respective accessories of the designation marking holder.

General ordering data

Туре	BZT 1 ZA WS 10/5	Version
Order No.	<u>1805520000</u>	Accessories, Marker holder
GTIN (EAN)	4032248270248	
Qty.	100 pc(s).	
Туре	BZT 1 WS 10/5	Version
Type Order No.	BZT 1 WS 10/5 <u>1805490000</u>	Version Accessories, Marker holder
	· · · · · · · · · · · · · · · · · · ·	

Custom printing

F	
h	
F	0000000
ŀ	
F	0000000
F	00000009
F	
h	
-	

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data Type DEK 5/5 MC SDR Version Order No. 1609810000 Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00 GTIN (EAN) 4008190456597 Weidmueller, To customer specification Oty. 200 pc(s). 200 pc(s).

Creation date March 12, 2024 4:08:45 PM CET

Accessories

Blank

1	L	L	E	L	Ŀ	L	L	1
E	L	L	Ŀ	Ŀ	Ŀ	L	Ŀ	1
	Т	Т	T.	T.	T.	Ŀ	1	1
E	T	T	T	L	T.	Ŀ	L	1
1	T	Т	Г	T.	Т	Ŀ	L	1
E	Т	T	Т	Τ.	Τ.	Ŀ	L	1
E	Т	Т	Τ.	L	T.	Ι.	T]
	Т	Т	Г	T	Г	T	Г	1
E	Г	T	T	Г		Г	L]
10	T	T	T	T	T	Т	T	1



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

	0	
Туре	DEK 5/8 MC NE WS	Version
Order No.	<u>1856740000</u>	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
GTIN (EAN)	4032248400850	Weidmueller, white
Qty.	800 pc(s).	

Accessories

DEK 5/6





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wearresistant labelling. A print resolution of 300 dpi also produces a very legible script. **Your benefits with MultiMark**

. Firms la stat an al structula in vicetina a

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

General ordering data

Туре	DEK 5/6 MM WS	Version
Order No.	<u>2007120000</u>	Dekafix, Terminal marker, 5 x 6 mm, Weidmueller, white
GTIN (EAN)	4050118392104	
Qty.	600 pc(s).	

Testsockets



Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

Туре	STB 16/D7/4/M4 SAK35	Version
Order No.	<u>0140200000</u>	SAK Series, Socket
GTIN (EAN)	4008190134884	
Qty.	50 pc(s).	

Accessories

Blank

T	ELLELLE]
Ľ	SECONDECES
	CEREBELEELS
Ľ	CELEBERE
Ľ	Internet I
Ľ	
Ľ	
Ľ	
r	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/5 MC NE WS	Version
Order No.	<u>1609801044</u>	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397111	Weidmueller, white
Qty.	1,000 pc(s).	

Screws



Depending on the terminal block or also accessories, we offer different types of screws as additional items or also spare parts.

Туре	BFSC M4X32 PA/NA	Version
Order No.	<u>0129100000</u>	Accessories, Mounting screw, for cross-connection link
GTIN (EAN)	4008190020842	
Qty.	100 pc(s).	
Туре	BFSC M4X30	Version
Type Order No.	BFSC M4X30 0267100000	Version Accessories, Mounting screw, for cross-connection link

Accessories

DEK 5/8





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wearresistant labelling. A print resolution of 300 dpi also produces a very legible script. **Your benefits with MultiMark**

- Finne hadden datum blan min tin m

- Firm hold and durable printing
- · Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

General ordering data

Туре	DEK 5/8 MM WS	Version
Order No.	<u>2007130000</u>	Dekafix, Terminal marker, 5 x 8 mm, Weidmueller, white
GTIN (EAN)	4050118392012	
Qty.	500 pc(s).	

QL / SAK 35



Screwable cross-connections are easy to mount and de mount. Thanks to the big contact surface, even high currents can be transmitted with maximum contact reliability.

Туре	QL 4 SAK35	Version
Order No.	<u>0123800000</u>	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190165390	poles: 4
Qty.	20 pc(s).	
Туре	QL 10 SAK35	Version
Type Order No.	QL 10 SAK35 0338600000	Version SAK Series, Cross-connector, for cross-connection link, Number of

Accessories

SAK 35/EN



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Туре	QL 2 SAK35	Version
Order No.	<u>0123600000</u>	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190092566	poles: 2
Qty.	20 pc(s).	
Туре	QL 3 SAK35	Version
Type Order No.	QL 3 SAK35 0123700000	Version SAK Series, Cross-connector, Cross-connector, Number of poles: 3

Blank

 sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers. Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths. Large range of ready-to-use markers Strips for fast installation Terminal markers, suitable for all Weidmüller cable connectors Available as blank MultiCard or with standard printing 		The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic
 sequences and covers a wide range of ready-printed markers. Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths. Large range of ready-to-use markers Strips for fast installation Terminal markers, suitable for all Weidmüller cable connectors 		
 markers. Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths. Large range of ready-to-use markers Strips for fast installation Terminal markers, suitable for all Weidmüller cable connectors 		
 Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths. Large range of ready-to-use markers Strips for fast installation Terminal markers, suitable for all Weidmüller cable connectors 	TATA TATA IN IN IN IN IN	
 printing is easy to read, rich in contrast and available in various widths. Large range of ready-to-use markers Strips for fast installation Terminal markers, suitable for all Weidmüller cable connectors 	TELEVISION DE LA CONTRACTÓ DE L	
 in various widths. Large range of ready-to-use markers Strips for fast installation Terminal markers, suitable for all Weidmüller cable connectors 		Strips for fast installation in only one work step. The
 Large range of ready-to-use markers Strips for fast installation Terminal markers, suitable for all Weidmüller cable connectors 	TO STORE THE REPORT OF	
 Strips for fast installation Terminal markers, suitable for all Weidmüller cable connectors 		in various widths.
 Terminal markers, suitable for all Weidmüller cable connectors 		 Large range of ready-to-use markers
connectors		 Strips for fast installation
 Available as blank MultiCard or with standard printing 		
		 Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

 Type
 DEK 5/6 MC NE WS
 Version

 Order No.
 1609820000
 Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

 GTIN (EAN)
 4008190203436
 Weidmueller, white

 Qty.
 1,000 pc(s).

Accessories

Custom printing

1	L			c	1
E	L				
	Т.,				
E					
E	T				
E	1				1
E	1				
	Γ				
°E	1				2
1					



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

	oraoning aata	
Туре	DEK 5/8 PLUS MC SDR	Version
Order No.	<u>1046370000</u>	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
GTIN (EAN)	4032248782079	Weidmueller, To customer specification
Qty.	160 pc(s).	
Туре	DEK 5/8 MC SDR	Version
Order No.	1856750000	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
oraci No.	1000700000	Dekana, reminarmarker, 5 x 6 mm, Filch in mm (F). 6.00
GTIN (EAN)	4032248400867	Weidmueller, To customer specification

Accessories



	1
iona and	ł
	1
0000009	1
	1
10000000	1
00000009	1
	1
11111111111	1
	0



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/6 MC SDR	Version
Order No.	<u>1609830000</u>	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4008190456603	Weidmueller, To customer specification
Qty.	200 pc(s).	

SAK-Series



A partition plate is used for the optical separation of circuits or used for electrical isolation from neighbouring cross-connectors. In contrast to the end plate, the contour can be larger than the adjacent terminal blocks. However, it should not be smaller, as otherwise the required clearance and creepage distances within the application can no longer be maintained.

Туре	TW SAK35	Version
Order No.	<u>0304360000</u>	SAK Series, Partition plate, 1.5 mm, beige, Direct mounting
GTIN (EAN)	4008190038885	
Qty.	20 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Connection sleeves



General ordering data

Туре	VH 17/8.2/5.2	Version
Order No.	0267000000	SAK Series, Connecting sleeve, for cross-connection link, Number of
GTIN (EAN)	4008190146986	poles:
Qty.	50 pc(s).	

Plus

E	1	L	I.	Ŀ	L	L	L	Ţ?
h	1	1	Ŀ	Ŀ	1.	Ŀ	1.	ł.
÷	1	1	Ŀ	Ŀ	Ŀ	Ŀ	1	ţ.
į.	P	1	Ŀ	Ŀ	Ŀ	Ŀ	1	ŧ.
	1	1	Ŀ	1	1	Ŀ	1	1
P			I	Ŀ	1	1	1	1
1		1			I.	I.	1	1
F				1	1	1	1	١.
r			L		1	1	1	ſ
								T

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	DEK 5/8 PLUS MC NE WS	Version
Order No.	<u>1046350000</u>	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
GTIN (EAN)	4032248782055	Weidmueller, white
Qty.	800 pc(s).	

Accessories

SAK 35/EN



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

6	P	S	Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.
	ordering data	Manai an	
Type		Version	
Order No.	0299600000	Accessories, Test plug	
GTIN (EAN)	4008190074043		
GHN (EAN)			