

**H4,0/20DS GR****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



- Polypropylene conical cable entry funnel
- Heat-resistant up to 105°C

For conductors from 0.5 – 10.0 mm<sup>2</sup> (AWG 20-7)

Material: E-Cu, tin galvanised

Dimensional tolerance acc. to DIN 46228 sect. 4

**General ordering data**

Version	Wire-end ferrule, Standard, 15 mm, 12 mm, grey
Order No.	<a href="#">9203630000</a>
Type	H4,0/20DS GR
GTIN (EAN)	4032248565078
Qty.	500 pc(s).
Packaging	loose

Creation date March 12, 2024 12:46:42 PM CET

Catalogue status 09.03.2024 / We reserve the right to make technical changes.

## H4,0/20DS GR

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

Net weight 0.26 g

## Technical data

Description of article	Wire end ferrule with plastic collar, special size, grey	Version	Standard

## Wire-end ferrules

Collar diameter (D2)	4.7 mm	Colour code	Miscellaneous
Conductor cross-section	4 mm <sup>2</sup>	Contact surface diameter (D1)	2.9 mm
Contact surface length (L2)	12 mm	L1 in mm	20 mm
Metal sleeve thickness (S1)	0.2 mm	Plastic collar thickness (S2)	0.5 mm
Stripping length	15 mm	Wire connection cross section AWG, max.	AWG 12

## Classifications

ETIM 6.0	EC000005	ETIM 7.0	EC000005
ETIM 8.0	EC000005	ETIM 9.0	EC000005
ECLASS 9.0	27-40-02-01	ECLASS 9.1	27-40-02-01
ECLASS 10.0	27-40-02-01	ECLASS 11.0	27-40-02-01
ECLASS 12.0	27-40-02-01	ECLASS 13.0	27-40-02-01

## Approvals

ROHS Conform

## Downloads

Engineering Data	<a href="#">CAD data – STEP</a>
User Documentation	<a href="#">Technical information - EN</a> <a href="#">Technical information - DE</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>
Brochures	

**Data sheet**

**H4,0/20DS GR**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

**Drawing**

